

# 17" Open Frame Touch Monitor

**OTL173-RPC03-UCD**  
**Monitor Datasheet**  
**Rev:1.1**

## Specification:

Model (GT)	OTL173-RPC03-UCD
Display Type	17" Active Matrix TFT LCD
Case/Bezel Color	Black
Stand	No Stand
Aspect Ratio	5:4
Active Display Area	LCD Panel: 337.920mm(H) × 270.336mm(V)
Native Resolution	1280 × 1024 @ 60 Hz
Other Supported Resolutions	640 × 480 @ 60 / 72 / 75 Hz 640 × 480 @ 67 Hz 720 × 400 @ 70 Hz 800 × 600 @ 56 / 60 / 72 / 75 Hz 832 × 624 @ 75 Hz 1024 × 768 @ 60 / 70 / 75 Hz 1152 × 864 @ 75 Hz 1280 × 960 @ 60 Hz 1280 × 1024 @ 60 / 75 Hz
Pixel Response Time (Typ.)	5 ms
Colors	16.7 million
Brightness (Typ.)	LCD Panel: 250 cd/m <sup>2</sup>
Contrast Ratio (Typ.)	1000:1
Viewing Angle (from centre, CR>10)	Horizontal (left/right): 170° (85°/85°) Vertical (up/down): 160° (80°/80°)
Input Video Format	RGB Analog / DVI Video
Input Video Signal Connector	VGA / DVI-D
Input Frequency	Horizontal: 30 to 82 kHz Vertical: 50 to 75 Hz
Touch Technology	Projected Capacitive Touch (P-Cap)
Touch Point	MAX: 10 points
Touch Interface	USB
Touch Screen Type	Tempered Anti Reflective (Optional) Anti Rlare(Optional)
On Screen Display (OSD)	Control (back): Power, Menu, Up, Auto, Down
Power Supply	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ± 5%
Input Connector	DC: Coaxial power jack (2.5 mm pin diameter, 5.5 mm barrel diameter, 11.5 mm barrel length)
Power Consumption (Max)	LED: 20 W
Monitor Dimensions	383.72mm(W) × 315.72mm(H) × 41mm(D)
Shipping Carton Dimensions	443mm(W) × 363mm(H) × 545mm(D)

( 4units in 1 carton )	
Weight (Approximately)	Monitor/Shipping (Approximately): 4.6/24kg ( 4units in 1 carton )
Mounting Options	Side Mount, VESA Mount 75 mm & 100 mm
Sealing	Touchscreen sealed to bezel Touchscreen sealed to LCD panel
Temperature Range	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 60°C (-4°F to 140°F)
Relative Humidity	Operating: 20%-80% Storage: 10%-90%
Warranty	3 years LCD panel: 1 year Touchscreen: 1 year MTBF: 50,000 hours demonstrated (Backlight Lamp Life, Hrs to 1/2 brightness)
Agency Approvals	FCC, CE, CCC

**MTBF (Mean Time Between Failures)**

An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit's reliability; thus MTBF is not, and should not be construed as, a warranty measurement.

General Touch Co.Ltd. reserves the right to change or update the information contained in this document without notice, and also have this right to discontinue or limit the production and distribution of any products.