


11.6” Zero-bezel SAW Touch Monitor

11.6” Surface Acoustic Wave Touch Monitor iSurface(zero-bezel)

 This is a new series of GeneralTouch' s zero-bezel touch monitor. Employing iSurface (Zero-bezel Surface Acoustice Wave) technology. It not only inherits the advantages of traditional SAW products, such as high reliability, high durability, high clarity and scratch resistance, but also has a flat gorgeous appearance . Aluminum alloy shell with a matte surface, gives a strong metallic feel. The LED backlight module provides a slim look, longer life, and lower power consumption for the touch monitor. It's the best choice for various public applications such as self-service terminals, kiosks, interactive digital signage etc.

Features & Applications

Features

- ◆ Zero-bezel SAW technology(iSurface)
- ◆ Pure glass touchscreen delivers superior image quality
- ◆ gorgeous appearance
- ◆ Continues to work even with scratches
- ◆ Easy integration and low maintenance
- ◆ Excellent performance, accuracy and reliability with drift-free operation

Applications

- ◆ Self-service terminals
- ◆ Ticketing machines
- ◆ Gaming machines
- ◆ Retail Point-of-Sale (POS) terminals
- ◆ Transportation Point-of-Information (POI)
- ◆ Office automation

SPECIFICATIONS

Name	11.6 Inch Open Frame Touch Monitor (zero-bezel)	
Model	OTL11D65-RZ03-UD	
LCD Panel Parameters		
• Display Ratio	16:9	
• Backlight Type	LED	
• Active Display Area	256.90mm*144.50mm	
• Pixels H x V	1920*1080	
• Response Time(typ.)	26ms	
• Support Color	16.7M	
• White Luminance(typ.)	300cd/m2	
• Contrast Ratio(typ.)	800:1	
• Viewing Angle(cr≥10)	Horizontal: 160°(80°/80°) (Typ.)	Vertical: 160°(80°/80°) (Typ.)
• Vertical Frequency(typ.)	60Hz	
• Led life time(typ.)	30000Hrs (Brightness of LED becomes to 50% of its original value)	
Touch Screen Parameters		
• Touch Technology	Surface Acoustic Wave(SAW)	
• Active Touch Area	258.30mm*145mm	
• Glass Thickness	3mm	
• Anti-Glare	Gloss :100± 15	
• Touch Response Time	10.4ms	
• Light Transmission	90%	
• Surface Hardness	Mohs' hardness rating of 7	
• Touch-Screen Interface	USB	
Touch Monitor Parameters		
• Mounting Options	VESA Mount, 75mm*75mm	
• Video Input Format	VGA/HDMI	
• Outline Dimensions	TBD	
• Power Supply	External Adapter:100-240VAC,50-60Hz Input Voltage Range: +12VDC ± 5%	
• On Screen Display (OSD)	Control(back): Power, Menu, Up, Down, Auto	
• Power Consumption(Max)	20W	
• Packing size	TBD	
• Weight	Monitor/Shipping (Approximately):TBD	
• Temperature Range	Operating: 0°C-40°C,storage: -20°C-60°C	
• Humidity (Non Condensing)	Operating: 20%-80%,storage: 10%-90%	
• MTBF	50000Hrs(Mean Time Between Failures)	
• Agency Approvals	TBD	
• Warranty	3years(LED panel 1 year)	

Item	Version	Date	Description	Changed by
1	Preliminary	2016/08/11	First Release	Long Kou
2				
3				

Go to www.generaltouch.com for more products and information, or contact us. General Touch Co., Ltd. reserves the right to change or update the information contained in this document without notice, and also has the right to discontinue or limit the production and distribution of any products.

Tel: 0086-28-85124114
Fax: 0086-28-85124115
E-mail: sales@generaltouch.com
<http://www.generaltouch.com>